

INSULATED ROLL

RANGE CHART

Model	Outer dimensions			Inner dimensions			Weight	Volume	K value
	Width	Length	Height	Width	Length	Height			
ROLL 220	600 mm	800 mm	1130 mm	430 mm	620 mm	830 mm	60 Kg	221 litre	0,34 W/M ² x°C
ROLL 300	715 mm	810 mm	1140mm	556 mm	635 mm	845 mm	70 Kg	298 litre	0,38 W/M ² x°C
ROLL 370	600 mm	800 mm	1670 mm	430 mm	620 mm	1370 mm	80 Kg	365 litre	0,37 W/M ² x°C
ROLL 500	715 mm	850 mm	1700 mm	545 mm	665 mm	1380 mm	95 Kg	500 litre	0,34 W/M ² x°C
ROLL 550	660 mm	950 mm	1855 mm	468 mm	770 mm	1528 mm	100 Kg	550 litre	0,30 W/M ² x°C
ROLL 580	715 mm	810 mm	1900 mm	550 mm	640 mm	1600 mm	100 Kg	563 litre	0,35 W/M ² x°C
ROLL 670	800 mm	1030 mm	1720 mm	610 mm	865 mm	1280 mm	130 Kg	675 litre	0,30 W/M ² x°C
ROLL 780	800 mm	1000 mm	1900 mm	610 mm	820 mm	1535 mm	130 Kg	768 litre	0,30 W/M ² x°C
ROLL 900	800 mm	1200 mm	1860 mm	610 mm	1000 mm	1493 mm	135 Kg	910 litre	0,27 W/M ² x°C
ROLL 1000	1000 mm	1200 mm	1680 mm	805 mm	1000 mm	1340 mm	145 Kg	1079 litre	0,31 W/M ² x°C
ROLL 1400	1000 mm	1200 mm	2000 mm	805 mm	1000 mm	1695 mm	165 Kg	1364 litre	0,31 W/M ² x°C

Tel : + 33 (0)4 77 906 863

Fax : + 33 (0)4 77 903 495

www.olivo.fr



LEADER IN INSULATED CONTAINERS