

BAC ISOTERMICO

TABELLA DELLA GAMMA

┌ **Dimensioni esterne** ┐

┌ **Dimensioni interne** ┐

Modello	Larghezza	Profondità	Altezza	Larghezza	Profondità	Altezza	Peso	Volume	Coef.K
BAC 50	610 mm	410 mm	485 mm	480 mm	280 mm	330 mm	17 Kg	44 litri	0,46 W/M ² x°C
BAC 55	600 mm	500 mm	580 mm	415 mm	315 mm	410 mm	16 Kg	53 litri	0,38 W/M ² x°C
BAC 120	765 mm	600 mm	614 mm	610 mm	445 mm	430 mm	30 Kg	117 litri	0,36 W/M ² x°C
BAC 130	800 mm	600 mm	715 mm	520 mm	410 mm	620 mm	31 Kg	138 litri	0,40 W/M ² x°C
BAC 150	800 mm	640 mm	660 mm	625 mm	470 mm	480 mm	32 Kg	141 litri	0,34 W/M ² x°C
BAC 160	800 mm	600 mm	1050 mm	580 mm	370 mm	700 mm	50 Kg	150 litri	0,25 W/M ² x°C
BAC 250	980 mm	900 mm	650 mm	800 mm	720 mm	455 mm	58 Kg	262 litri	0,35 W/M ² x°C
BAC 260	996 mm	926 mm	810 mm	800 mm	720 mm	455 mm	73 Kg	262 litri	0,35 W/M ² x°C
BAC 420	1200 mm	800 mm	1050 mm	1000 mm	600 mm	700 mm	90 Kg	420 litri	0,27 W/M ² x°C
BAC 480	1200 mm	1000 mm	970 mm	1000 mm	800 mm	600 mm	112 Kg	480 litri	0,27 W/M ² x°C
BAC 600	1200 mm	1200 mm	970 mm	1000 mm	1000 mm	600 mm	122 Kg	600 litri	0,26 W/M ² x°C

Tel : + 33 (0)4 77 906 863

Fax : + 33 (0)4 77 903 495

www.olivo.fr



LEADER IN INSULATED CONTAINERS